AD-A277 545

25 030

NSN 7540-01-280-5500

1ENTATION PAGE

Form Approved
OMB No. 0704-0188

Standard Form 293 (Rev. 2-89)

stimated to average 1 hour per resonne, including the time for reviewing instructions, searching existing data sources, and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this time, this burden, to Washington neadquarters services, Directorate for Information Operations and Reports, 1215 Jefferson 02, and to the Office of Management and Budget, Paperwich Reduction Project (0704-0188), Washington, 07, 20503.

AUCHCY USE ONLY (Leave blank		3. REPORT TYPE AND DATE Interim 90 APR	
4. TITLE AND SUBTITLE			DING NUMBERS EN HUA
NEURO-TRIGGERED TRA	AINING		9620-90-c-0026
6. AUTHOR(S)			110aF
Alan S. Gevins, PI Harrison Leong			313
7. PERFORMING ORGANIZATION NAI	ME(S) AND ADDRESS(ES)	8. PER	FORMING ORGANIZATION
EEG Systems Labora 51 Federal Street, San Francisco, CA	Suite 401		DSR-TR- 94 0104
9. SPONSORING/MONITORING AGEN USAF, AFSC Air Force Office o Bldg. 410 Bolling AFB, DC 20	f Scientific Resear		94-09366
11. SUPPLEMENTARY NOTES 12a. DISTRIBUTION/AVAILABILITY S	MAR	2.8 1994 D	DISTRIBUTION CODE
AFOSR APPROVED COMMISSION AFOSR APPROVED AFOSR APPR	This docution public distribution	ment has been approved telease and sale; it in it unlimited.	
We made progress in sever system and moved it onto a computational headroom; attention associated with he remove signal contaminar specifically eye blinks, eye and piloted a new task for heightened ability to receiv sponsored study of working completed statistical analysponsored experiment on the	new platform for incre 2) performed pilot recor- ightened ability to receive its typically generated a movements, and muscle training the production are and retain information are memory; the manuscustes and figures and neg	ased number of channels rdings seeking simpler Eve and retain information; by stationary subjects to tension on the head; 4) n of a preparatory attention. We also revised a manuscript has been accepted farly completed a manuscript arly completed a manuscript arly completed a manuscript arly completed a manuscript has been accepted to the farly completed a manuscript has been accepted to the farly completed a manuscript has been accepted to the farly completed a manuscript has been accepted to the farly completed a manuscript has been accepted to the farly completed a manuscript has been accepted to the farly completed a manuscript has been accepted to the farly completed a manuscript has been accepted to the farly completed a manuscript has been accepted to the farly completed a manuscript has been accepted to the farly completed a manuscript has been accepted to the farly completed a manuscript has been accepted to the farly completed a manuscript has been accepted to the farly completed a manuscript has been accepted to the farly completed a manuscript has been accepted to the farly completed a manuscript has been accepted to the farly completed a manuscript has been accepted to the farly completed a manuscript has been accepted to the farly completed a manuscript has been accepted to the farly completed to th	and a needed increase in EG measures of focused 3) implemented filters to doing laboratory tasks, designed, implemented, ive state associated with script on a prior AFOSR-for publication. We also cript on a prior AFOSR-for publication as a prior AFOSR-for publication.
		DTIC QU	MINT HOUSESTED 1
BRAIN ACTIVITY, C	OGNITION, LEARNING		15. NUMBER OF PAGES 6 16. PRICE CODE
17. SECURITY CLASSIFICATION III OF REPORT Ünelässified	8. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT Unlimited

11.17

1993

Best Available Copy

NEURO TRIGGERED TRAINING

AFOSR Contract F49620-90-C-0026

INTERIM TECHNICAL REPORT 1 APR 92 to 31 MAR 93

PREPARED FOR

Dr. John Tangney
Directorate of Life Sciences
Air Force Office of Scientific Research
Bolling AFB, D.C. 20332-6448

APPROVED BY

Alan Gevins, Director

Accesion For			
NTIS CRASI V DTIC TAS, TO Unamnounced E) Justification			
By Distribution /			
Availability Codes			
Dist	Avail a. d j or Special		
A-1			

The views and conclusions in this document are those of the authors and should not be interpreted as necessarily representing the official policies or endorsements, either expressed or implied, of the Air Force Office of Scientific Research or the U.S. Government.

PERSONNEL

Alan Gevins, Principal Investigator
Harrison Leong, Neuroengineer
Michael Smith, Neuroscientist
James Johnston, Biophysicist
Bill O'Connor, Programmer
Jeffrey Bennett, Research Associate
Paul Brickett, Psychophysiologist (memory and language manuscripts)
Brian Cutillo, Cognitive Scientist (memory and language manuscripts)

PUBLICATIONS IN THE PAST YEAR

- Gevins, A.S. and Cutillo, B.C. (In press, 1993) Neuroelectric evidence for distributed processing in human working memory. *EEG Clin. Neurophysiol*.
- J. Le & A.S. Gevins (In press, 1993) Mothod to reduce blur distortion from EEGs using a realistic head model. *IEEE Transactions on Biomedical Engineering*.
- Gevins, A.S. (In press, 1993) High resolution evoked potentials of cognition. Brain Topography.
- Gevins, A.S., et al. (Submitted, 1993) Imaging the spatiotempral dynamics of cognition with high resolution evoked potential methods. *Human Brain Mapping*.
- Gevins, A.S., et al. (In press, 1993) High resolution EEG: 124-channel recording, spatial enhancement and MRI integration methods. *EEG Clin. Neurophysiol*.
- Gevins, A.S., et al. (In Press, 1993) High resolution evoked potential technology for imaging neural networks of cognition. In: Thatcher, R.W., et al. (Eds.) Functional Neuroimaging: Technical Foundations. Academic Press, Inc.: Orlando.
- Gevins, A.S. (In press, 1993) High resolution EEG. Brain Topography.
- Wikswo J.P., Gevins, A.S., Williamson S. J. (In press) The future of the EEG and MEG. EEG Clin. Neurophysiol.
- Gevins, A.S., et al. (1992) The future of high-resolution EEGs in assessing Neurocognitive effects of mild head injury. In: D. Katz & M. Alexander (Eds), *Journal of Head Trauma Rehabil.*, 7(2), pp. 78-90.

NEURO-TRIGGERED TRAINING (TRIGGER)

The objective of the Trigger project is to determine the feasibility of a method to accelerate the learning of a simple cognitive task and to optimize performance by delivering stimuli at instants when preparatory attentional cortical networks are optimally activated. We plan to achieve this objective by determining the prestimulus EEG patterns associated with a subject's accurate task performance using neural-network pattern recognition, and then training the subject to produce those patterns on a single-trial basis.

Personnel Changes

Brian Cutillo, previously Co-PI, is no longer involved with the project. Harrison Leong, a neuroengineer who is experienced in neural network pattern recognition, is now managing the day-to-day conduct of the project. Michael Smith, a cognitive neuroscientist specializing in the neuropsychology and neurophysiology of memory and attention, is working on task and experimental design and data analysis. The programming is being performed by Jim Johnston and Bill O'Connor who are both experienced in PC programming. Johnston is additionally an expert on EEG feedback systems. Jeffrey Bennett is assisting with data collection and analysis.

System Development

The first Neurotrigger system we implemented was based on commercial software and hardware including the EEGSYS program, Labmaster digitizer, and Beckman amplifiers. Running on a 33 MHz PC486, the system was benchmarked to determine processor time available for real time signal analysis after handling electrophysiological datá collection and task stimulus presentation. Headroom was less than 0.25 Mflops. This was deemed insufficient for real time artifacting and other signal processing needed for neurotriggering. At this juncture, an electrophysiological data collection system (SMARTHAT) being developed by our sister organization, SAM Technology, was far enough along so that it was most cost effective to obtain the computational headroom we needed by modifying a SMARTHAT system to perform neurotriggering. Benchmarks indicate it yields approximately 2.25 Mflops of computational headroom; this will suffice for the artifact minimization and signal processing we will require. (A further increase in computational headroom can easily be obtained by changing the processor to a 66 MHz PC486.) Additional benefits include higher noise immunity due to on-the-head pre-amplification, simplified usage by obviating the need to prepare the scalp at each electrode site, more EEG channels (up to 32), and high level inputs for sources such as response transducers and accelerometers for use in detecting and minimizing head movement artifact. SMARTHAT also provides a library of software functions that can be used to express a wide variety of tasks with little concern for how to make the tasks run simultaneously with electrophysiological data collection.

The feasibility of using this system for the Neurotrigger project was verified. A simple CNV task was programmed (visual cue followed by a stimulus that required right or left hand response) and used as a final test of the system. Averages were computed and CNVs were observed where expected.

Real-time Artifact Processing

Algorithms for minimizing EEG contamination caused by eye movements and blinks and muscle tension were developed at SAM Technology and are being made available for this project. These contaminants are those most likely to compromise the accuracy of neurotriggering in controlled conditions where the subject is stationary and doing laboratory tasks designed to minimize sources of EEG contamination. The algorithms were designed for use in real-time and were rapidly developed using MATLAB from Mathworks, Inc. The next step is to translate MATLAB code into C and/or assembly language, integrate this software with the SMARTHAT software, and test.

Pilot Recordings

A series of recordings with a variety of task variations were made to find a simple EEG signal of heightened, focused attention. Following the lead of previous research (reviewed in Gevins and Schaffer, 1980), we sought a reliable diminution of alpha power and enhanced theta power with the onset of focused attention. In one task, subjects were instructed to try to mentally move a cursor by sharply focusing their attention on it; the cursor remained stationary. In a similar task, the cursor was programmed to move in such a way that it appeared to be under neurotriggered control. Although we did observe expected changes in alpha and theta power, we concluded that more than a second of data would be needed to reliably detect changes in these parameters. In particular, we observed that the amplitude, duration, and frequency of alpha bursts decreased when the subject's attention was narrowly focused; but, there was no clear, reliable abrupt change in alpha within ± 0.5 seconds of when the onset of this mental state was to occur. The time scale for reliable detection would be too long for neurotriggering, which requires a decision in about 500 msec. Hence, we decided it would be most fruitful to focus our efforts on finding single-trial CNV features that characterize optimal states of preparatory attention.

Improvements to the Experimental Approach

We have improved our approach by opting for training a preparatory attentional state that is more cognitively loaded than motor priming. Specifically, we plan to focus on training the ability to produce a heightened state of concentration to receive and retain information. In addition, we will provide feedback training that better adapts to the subject's immediate needs by using continuously graded neurotriggering instead of binary triggering: Instead of waiting for the subject to produce a "correct" neuroelectric pattern before giving a stimulus, the quality of the stimulus will be modulated based on the degree to which the subject produces optimal neuroelectric patterns and, furthermore, stimulus quality will be a factor in the overall measure of performance upon which a monetary bonus will be computed. We will use the Sternberg memory scanning task (Sternberg, 1966) in which a set of letters to be remembered is briefly presented, followed by probes that test retention of this information. The task has a known CNV to the set of letters which has been observed to be predictive of performance accuracy (Morgan et al., 1992). The duration of the memory set will be modulated based on an electrophysiologic assessment of the degree to which the subject is prepared to receive and absorb the information presented. The maximum task performance level achieved and the time required to achieve this level will be measured. These measures will be compared with those achieved when training is based on modulating the letter set duration using behavioral performance or randomly. Separate groups of subjects will be used for each condition. Subjects will be carefully selected for equivalent initial performance on the task and percent change in performance will be used to compare the effects of each condition. This experiment permits us to observe, in one example, the value of instantaneous adaptation of stimulus presentation (neurotriggering) compared to adapting over a longer time frame (adaptation based on behavioral data only) and no adaptation to subject state. It may be necessary to increase the difficulty of the task so that the training effects are large enough. Variations of the task that are cognitively more difficult can be simply constructed by changing the information that must be retained and the way retention is tested; for example, paired associates can be used in place of letters.

Next Steps

- 1) Gather more pilot data and complete analysis of this data to determine single trial CNV signal features that will be used for neurotriggering;
- 2) Enhance system software to perform real-time artifact contaminant minimization and, we anticipate, estimate regional single-trial CNV amplitude relative to a baseline.
- 3) Modify the Stemberg task implementation to provide adaptive control of its stimulus parameters (memory set duration) by control signals derived from electrophysiological data or behavioral data.
- 4) Test the fully implemented system and pilot the three training conditions.
- 5) Modify the system and task as necessary, i.e. increase task difficulty.
- 6) Obtain and analyze recordings from six subjects.

PUBLICATION OF RESULTS OF WORKING MEMORY STUDY

A paper describing the results of a prior AFOSR-sponsored pilot study on working memory has been accepted for publication in The EEG Journal.

MANUSCRIPT OF RESULTS OF LANGUAGE STUDY

We also completed statistical analyses and figures and nearly completed a manuscript on a prior AFOSR-sponsored experiment on the neurophysiology of language. The manuscript will shortly be

submitted to The EEG Journal.

REFERENCES

Gevins, A.S., and Schaffer, R.E., (1980), "A critical review of electroencephalographic (EEG) correlates of higher cortical functions," CRC Critical Rev. in Bioeng., Oct, pp113-164.

Morgan, J.M., Wenzl, M., Lang, W., Lindinger, G., & Deecke, L., (1992). Frontocentral DC-potential shifts predicting behavior with or without a motor task. Electroenceph. clin. Neurophysiol., 83, 378-388.

Stemberg, S., (1966), "High speed scanning in human memory, Science, v153, pp652-654.